

Replacement for Lead Acid, GEL or AGM in LFP Battery Solutions




PRODUCT FEATURES


Designed for your solar, RV and marine applications, BSLBATT's 24V 2560 Wh lead reformed battery lasts four times longer than lead-acid batteries and is maintenance-free, lightweight and simple to operate.

Our B-LFP24-100 is equipped with the industry's leading brand of LFP batteries, the safest lithium battery chemistry available today. So it's ideal for deep cycle applications such as trolling motors, RVs or boating that require large amounts of power for long periods of time.

CHARGE AND DISCHARGE CURVE



DIMENSION





Battery Model	B-LFP24-100

Nominal Voltage 25.6 V

Typical Capacity $100 \pm 1.5 \text{ Ah} \text{ (At 0.2C discharge rate)}$

Energy 2560 Wh

Discharge

Working Current 0.5 C

Maximum Current 1 C

Cut-off Voltage About 20 V

Charge

Voltage $28.8 \pm 0.2 \text{ V}$ Working Current0.5 CMax Charging Current $\leq 1 \text{ C}$ Charge ModeCC/CV, please use special lithium chargerCharging Cut-off CurrentAbout 5 A

Operation Temperature

Charge 0° C \sim +55 $^{\circ}$ C Discharge -20° C \sim +60 $^{\circ}$ C

Additional Data

Storage Temperature $-20^{\circ}\text{C} \sim +45^{\circ}\text{C}$ Discharging Inner Resistance $\leq 60 \text{ m}\Omega$

Protection Function Overcharge, over-discharge, over-current, short circuit and other protection functions

Output Mode M8 Terminal
Shell Material ABS

Weight Approx 19 Kg (Single weight)

Dimension (L*W*H) 483*172*240 (±2) mm

Modules In Series 2

Cycle ≥3500, 80%DOD (0.2C, 25°C)

Note: Parameters can be adjusted according to customer requirements











Facebook

Linkedin

Tiktok

Instagram

Youtube



Drop-in Replacement



Tier One, A+ LiFePO4 Cell Composition



5 Years Warranty Guarantee



Smart Hardware & Software Design



Long Service Life



Eco-Friendly